

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: IJMOPOX THINNER
 Article number: 804
 UFI: H9Q1-N0A1-2008-U85K

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 SU19 Building and construction work
 Product category PC9a Coatings and paints, thinners, paint removers
 Process category PROC19 Manual activities involving hand contact
 Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article
 ERC8c Widespread use leading to inclusion into/onto article (indoor)
 ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 Article category AC13 Plastic articles
 Application of the substance / the mixture See our technical datasheet for application details of this product.
 Thinner, Diluent

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: De IJssel Coatings BV, Centrumbaan 960, NL 2841 MH Moordrecht
 Tel: +31 182 372177, E-mail: info@de-ijssel-coatings.nl
 Further information obtainable from: Research and Development.


1.4 Emergency telephone number:

De IJssel Coatings BV, Tel. +31 182 372177, E-mail: safety@de-ijssel-coatings.nl
 Office hours: working days from 08:00 to 17:00 hrs.


*** SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture


Classification according to Regulation (EC) No 1272/2008

 GHS02 flame


Flam. Liq. 3 H226 Flammable liquid and vapour.

 GHS08 health hazard

Carc. 2 H351 Suspected of causing cancer.
 Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

 GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

 GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

 GHS07

Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

    
 GHS02 GHS05 GHS07 GHS08 GHS09

Signal word

Danger

Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.
 butan-1-ol
 4-methylpentan-2-one

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 60 (replaces version 59)

Revision: 18.07.2023

Trade name: IJMOPOX THINNER

(Contd. of page 1)

| | |
|----------------------------|--|
| · Precautionary statements | <p>H318 Causes serious eye damage. H351 Suspected of causing cancer. H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects.</p> <p>P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read carefully and follow all instructions. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations.</p> |
|----------------------------|--|

· 2.3 Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**· 3.2 Mixtures**

- Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

| | | |
|---|---|-----------|
| CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35 | Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H335-H336, EUH066 | 50 – 100% |
| CAS: 108-10-1 EINECS: 203-550-1 Index number: 606-004-00-4 Reg.nr.: 01-2119473980-30 | 4-methylpentan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Carc. 2, H351; ⚠ Acute Tox. 4, H332; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066 ATE: LC50/4 h inhalative: 11 mg/l | 25 – 50% |
| CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38 | butan-1-ol ⚠ Flam. Liq. 3, H226; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 10 – 25% |

- Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**· 4.1 Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media**

- Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.

(Contd. on page 3)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 60 (replaces version 59)

Revision: 18.07.2023

Trade name: IJMOPOX THINNER

(Contd. of page 2)

- For safety reasons unsuitable extinguishing agents: Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- Protective equipment: No special measures required.

*** SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures** Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- Storage: Requirements to be met by storerooms and receptacles: Store material in original, tightly closed containers in a cool, well-ventilated area in accordance with applicable (local) regulations. Depending on total volume stored, the storage area should comply with PGS15.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 - 30 °C
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| | | |
|---|--|--------------------------------|
| · Ingredients with limit values that require monitoring at the workplace: | | |
| 108-10-1 4-methylpentan-2-one | | |
| IOELV | Short-term value: 208 mg/m ³ , 50 ppm Long-term value: 83 mg/m ³ , 20 ppm | |
| · DNEL (Derived No Effect Level) for workers | | |
| 64742-95-6 Solvent naphtha (petroleum), light arom. | | |
| Dermal | Long-term - systemic effects, worker | 25 mg/kg bw/day (Worker) |
| Inhalative | Long-term - systemic effects, worker | 150 mg/m ³ (Worker) |
| 71-36-3 butan-1-ol | | |
| Inhalative | Long-term - local effects, worker | 310 mg/m ³ (Worker) |

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 60 (replaces version 59)

Revision: 18.07.2023

Trade name: IJMOPOX THINNER

(Contd. of page 3)

| | | |
|---|--|---|
| · DNEL (Derived No Effect Level) for the general population | | |
| 64742-95-6 Solvent naphtha (petroleum), light arom. | | |
| Oral | Long-term - systemic effects, general population | 11 mg/kg bw/day (General population) |
| Dermal | Long-term - systemic effects, general population | 11 mg/kg bw/day (General population) |
| Inhalative | Long-term - systemic effects, general population | 32 mg/m ³ (General population) |
| 71-36-3 butan-1-ol | | |
| Oral | Long-term - systemic effects, general population | 3.125 mg/kg bw/day (General population) |
| Inhalative | Long-term - local effects, general population | 55 mg/m ³ (General population) |
| · PNEC (Predicted No Effect Concentration) values | | |
| 71-36-3 butan-1-ol | | |
| Aquatic compartment - freshwater | | 0.082 mg/l (Freshwater) |
| Aquatic compartment - marine water | | 0.0082 mg/l (Marine water) |
| Aquatic compartment - water, intermittent releases | | 2.25 mg/l (Intermittent release water) |
| Aquatic compartment - sediment in freshwater | | 0.178 mg/kg sed dw (Sediment freshwater) |
| Aquatic compartment - sediment in marine water | | 0.0178 mg/kg sed dw (Sediment marine water) |
| Terrestrial compartment - soil | | 0.015 mg/kg dw (Soil) |
| Sewage treatment plant | | 2,476 mg/l (stp) |

· Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing
 - Wash hands before breaks and at the end of work.
 - Store protective clothing separately.
 - Avoid contact with the skin.
 - Avoid contact with the eyes and skin.
- Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Hand protection
 - Protective gloves
 - The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
 - Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
 - Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves
 - Nitrile rubber, NBR
 - The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - Recommended thickness of the material: ≥ 0.3 mm
- Penetration time of glove material
 - The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).
- For the permanent contact gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
- As protection from splashes gloves made of the following materials are suitable:
 - Nitrile rubber, NBR
- Not suitable are gloves made of the following materials:
 - Leather gloves
 - Strong material gloves
- Eye/face protection
 - Tightly sealed goggles

(Contd. on page 5)

Trade name: IJMOPOX THINNER

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

| | |
|--|--|
| · General Information | |
| · Physical state | Fluid |
| · Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | 114 – 117 °C |
| · Flammability | Flammable. |
| · Lower and upper explosion limit | |
| · Lower: | 0.7 Vol % |
| · Upper: | 9.4 Vol % |
| · Flash point: | 25 °C (Pensky Martens, ASTM D93) |
| · Auto-ignition temperature: | 340 °C |
| · Decomposition temperature: | Not determined. |
| · pH at 20 °C | 7 |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic at 20 °C: | 10 mPas (Brookfield, ASTM D1544) |
| · Solubility | |
| · water: | Not miscible or difficult to mix. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C: | 8 hPa |
| · Density and/or relative density | |
| · Density at 20 °C: | 0.839 g/cm ³ (DIN 51757, ASTM D 1298) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

· 9.2 Other information

| | |
|---|---|
| · Appearance: | |
| · Form: | Fluid |
| · Important information on protection of health and environment, and on safety. | |
| · Ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Solvent content: | |
| · Organic solvents: | 100.0 % |
| · VOC: | |
| · VOC (2004/42/EC): | 100.00 % |
| · Solids content: | 0.0 % |
| · Change in condition | |
| · Evaporation rate | Not determined. |

· Information with regard to physical hazard classes

| | |
|---|------------------------------|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Flammable liquid and vapour. |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

(Contd. on page 6)

Trade name: IJMOPOX THINNER

(Contd. of page 5)

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

| Components | Type | Value | Species |
|--|------|---------------|----------|
| ATE (Acute Toxicity Estimates) | | | |
| Oral | LD50 | 5,267 mg/kg | (Rat) |
| 64742-95-6 Solvent naphtha (petroleum), light arom. | | | |
| Oral | LD50 | > 6,800 mg/kg | (Rat) |
| Dermal | LD50 | > 3,400 mg/kg | (rab) |
| 108-10-1 4-methylpentan-2-one | | | |
| Oral | LD50 | 2,080 mg/kg | (Rat) |
| Dermal | LD50 | 16,000 mg/kg | (rab) |
| 71-36-3 butan-1-ol | | | |
| Oral | LD50 | 790 mg/kg | (Rat) |
| Dermal | LD50 | 3,400 mg/kg | (Rabbit) |

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Suspected of causing cancer.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation. May cause drowsiness or dizziness.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard May be fatal if swallowed and enters airways.

11.2 Information on other hazards

| |
|------------------------------------|
| · Endocrine disrupting properties |
| None of the ingredients is listed. |

SECTION 12: Ecological information

- **12.1 Toxicity**
- Aquatic toxicity: No further relevant information available.

| Type of test | Effective concentration | Method | Assessment |
|--|-------------------------|------------------|------------|
| ATE (Acute Toxicity Estimates) | | | |
| Inhalative | LC50/4 h | 27.7 – 55.3 mg/l | (ATE) |
| 64742-95-6 Solvent naphtha (petroleum), light arom. | | | |
| Inhalative | LC50/4 h | > 10.2 mg/l | (Rat) |
| 108-10-1 4-methylpentan-2-one | | | |
| Inhalative | LC50/4 h | 11 mg/l | (ATE) |
| | | 8.3 – 16.6 mg/l | (Rat) |
| 71-36-3 butan-1-ol | | | |
| Inhalative | LC50/4 h | 8,000 mg/l | (Rat) |

(Contd. on page 7)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 60 (replaces version 59)

Revision: 18.07.2023

Trade name: IJMOPOX THINNER

(Contd. of page 6)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- PBT: Not applicable.
- vPvB: Not applicable.
- **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- Remark: Toxic for fish
- Additional ecological information:
- General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

*** SECTION 13: Disposal considerations**

- **13.1 Waste treatment methods**
- Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| | |
|----------------------------|---|
| · European waste catalogue | |
| 08 00 00 | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS |
| 08 01 00 | wastes from MFSU and removal of paint and varnish |
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances |
| HP3 | Flammable |
| HP4 | Irritant - skin irritation and eye damage |
| HP5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity |
| HP7 | Carcinogenic |
| HP14 | Ecotoxic |

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.

*** SECTION 14: Transport information**

| | |
|---|--|
| · 14.1 UN number or ID number · ADR/RID/ADN, IMDG, IATA | UN1263 |
| · 14.2 UN proper shipping name · ADR/RID/ADN · IMDG · IATA | 1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS PAINT RELATED MATERIAL, MARINE POLLUTANT PAINT RELATED MATERIAL |
| · 14.3 Transport hazard class(es) · ADR/RID/ADN · Class · Label | 3 (F1) Flammable liquids. 3 |
| · IMDG, IATA · Class · Label | 3 Flammable liquids. 3 |
| · 14.4 Packing group · ADR/RID/ADN, IMDG, IATA | III |
| · 14.5 Environmental hazards: | Product contains environmentally hazardous substances: Solvent naphtha (petroleum), light arom. |

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 18.07.2023

Version number 60 (replaces version 59)

Revision: 18.07.2023

Trade name: IJMOPOX THINNER

(Contd. of page 7)

| | |
|---|--|
| · Marine pollutant: | Yes |
| · Special marking (ADR/RID/ADN): | Symbol (fish and tree) Symbol (fish and tree) |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E,S-E |
| · Stowage Category | A |
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR/RID/ADN | 5L |
| · Limited quantities (LQ) | Code: E1 |
| · Excepted quantities (EQ) | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS |

*** SECTION 15: Regulatory information**

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I
None of the ingredients is listed.
- Seveso category
E2 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
200 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII
Conditions of restriction: 3

| | |
|--|------------------------------------|
| · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II | None of the ingredients is listed. |
| · REGULATION (EU) 2019/1148 | |
| · Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3)) | None of the ingredients is listed. |
| · Annex II - REPORTABLE EXPLOSIVES PRECURSORS | None of the ingredients is listed. |
| · Regulation (EC) No 273/2004 on drug precursors | None of the ingredients is listed. |
| · Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors | None of the ingredients is listed. |

- National regulations:
- Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK | 100.0 |

(Contd. on page 9)

**Safety data sheet
according to 1907/2006/EC, Article 31**

Printing date 18.07.2023

Version number 60 (replaces version 59)

Revision: 18.07.2023

Trade name: IJMOPOX THINNER

(Contd. of page 8)

15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H351 Suspected of causing cancer.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH066 Repeated exposure may cause skin dryness or cracking.

- Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

| | |
|---|--|
| Flammable liquids | On basis of test data |
| Skin corrosion/irritation Serious eye damage/irritation Carcinogenicity Specific target organ toxicity (single exposure) | The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. |
| Aspiration hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard | Expert judgement |

- Department issuing SDS: Research and Development
- Contact: Saïda El Asjadi, tel: +31 182 372177, e-mail: safety@de-ijssel-coatings.nl
- Date of previous version: 28.01.2022
- Version number of previous version: 59
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Flam. Liq. 3: Flammable liquids – Category 3
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Carc. 2: Carcinogenicity – Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - Asp. Tox. 1: Aspiration hazard – Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

- Sources: Literature data and/or investigation reports are available through the manufacturer.
- * Data compared to the previous version altered.